

TFS28

Professional Compact Access Control System



**Auto-Push
Technology**

**Auto-Adapt
Sensor**



EM Card



Personal
Identity Number



USB Link



TCP/IP



RS232/485



USB Disk



Access
Control



Specifications

» Fingerprint Users	3,000/5,000
» Card User	3,000/5,000
» Password User	3,000/5,000
» Attendance Records	100,000
» Fingerprint Verification	Mode1:1, 1:N
» Working Mode	Offline/Online
» Verification	Fingerprint, ID Card, Password
» Combination	FP + Card, PIN + Card, FP + PIN + Card
» Verification Time	> 1.0s
» False Rejection Rate	< 0.01%
» False Acceptance Rate	< 0.0001%
» Fingerprint Sensor	Optical Sensor
» Screen	3 inches (Color Display)
» Display Language	English
» Communication	RS485, USB Drive/Link, TCP/IP
» Working Humidity	20%-60%
» Working Temperature	0°C-50°C
» Power Supply	12V DC
» Idle Current	400mA
» Working Current	500mA
» Sound Indicator	Buzzer, Voice
» Access Control	Built-in
» Access control	Directly control of door lock / Indirectly control of door lock via Wiegand access controller. Support 50 access time zones, combination identification, anti-pass back.
» Battery Backup	Optional
» Server Connection	Auto Push Technology